CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL

FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM





LISTING No. 7165-0410:0159 Page 1 of 2

CATEGORY: 7165 -- FIRE ALARM CONTROL UNIT (COMMERCIAL)

LISTEE: Hochiki America Corporation7051 Village Drive, Ste. 100, Buena Park, CA 90621-2268

Contact: Tony Lujan (714) 670-3248 Fax (714) 522-2268

Email: tlujan@hochiki.com

DESIGN: Model FireNet 4127 Analog Addressable fire alarm control unit. Automatic, manual, waterflow

and sprinkler supervisory service. Refer to the listee's data sheet for detailed product

description and operational considerations. System components:

<u>MODULE</u>	PART NO.	<u>DESCRIPTION</u>
FN-4127-BO	(K6002)	Control Board
FN-4127-IO	(K6006)	16 Channel Input/Output Board
FN-4127-CPA-BO	(K6001)	Front LCD Indicator Panel
FN-4127-SLC	(K6004)	Loop 3, 4 Board
FN-4127-NIC	(K6005)	Network Card
FN-PS402	(S402)	Power Supply
FN-DAC	(FN-DAC)	Digital Alarm Communicator
FN-ENC	(FN-ENC)	Enclosures
FN-ACC	(FN-ACC)	Battery/Accessory Enclosure
FN-CTM	(7000-00780)	City Tie Module
D9068	(D9068)	Bosch Digital Alarm Communication
		Transmitter
HMX-DP		Voice Evacuation System Distribution Panel
HMX-MP		Voice Evacuation System Master Panel
EVX-100		Audio Adjunct Module
EVX-RM		Remote Microphone

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes & ordinances,

and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, electrical rating, and UL label.

APPROVAL: Listed as fire alarm control unit for use with separately listed compatible initiating and

indicating devices. *Also suitable for high-rise applications.

These control units can generate the distinctive three-pulse Temporal Pattern Fire Alarm

Evacuation Signal as required per NFPA 72, 2002 Edition.

This control unit meets the requirements of UL-864, *9th Edition Standard

NOTE: 1. For Fire Alarm Verification Feature (Delay of fire alarm), the maximum

*Rev 6-24-2009 fm



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: July 01, 2021 Listing Expires June 30, 2022

Authorized By: **DAVID CASTILLO**, M.E., F.P.E.

Fire Engineering Division

Listing No. 7165-0410:0159

Page 2 of 2

Retard/Reset/Restart period must be adjusted to 30 seconds or less.

2. Combined with 7170-0410:170

*Rev 6-24-2009 fm



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: July 01, 2021 Listing Expires June 30, 2022

Authorized By: **DAVID CASTILLO,**, M.E., F.P.E.

Fire Engineering Division