



EOQF.S1383 Smoke-automatic Fire Detectors, Marine

[Page Bottom](#)

Smoke-automatic Fire Detectors, Marine

[See General Information for Smoke-automatic Fire Detectors, Marine](#)**HOCHIKI AMERICA CORP.**

S1383

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Application	Type	Compatibility Restriction	Range Min	(fpm) Max	Model
OAP	P	++	0	4000	SLV-24M

Base Models NS4-220 and NS4-220W are compatible with Model SLV-24M smoke detector head (++).

Base Models NS6-220 and NS6-220W are compatible with Model SLV-24M smoke detector head (++).

++Two-wire detector/base only for use with a control panel with which UL has determined compatibility by a review of circuit parameters.

Codes:

OAP-Open Area Protection

P-Photoelectric

[Last Updated](#) on 2008-10-22

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



FTAM.S1383 Gas and Vapor Detectors and Sensors

[Page Bottom](#)

Gas and Vapor Detectors and Sensors

[See General Information for Gas and Vapor Detectors and Sensors](#)

HOCHIKI AMERICA CORP.

S1383

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Carbon monoxide detector, Models ACD-V(a) (b), ACD-VW(a) (b), when programmed in the CO detection mode only through the FACP. For use with Models YBN-NSA-4 and HSB-NSA-6, Detector Base, Model ASB, Sounder Detector Base, Models SCI-B4, and SCI-B6, Isolator Detector Base, and Model ASBL, low frequency 520Hz, addressable Detector Sounder Base. This detector model is Listed for use with this manufacturer Fire Alarm Control panel as identified in the Fire Alarm Control Panel Manual. This detector operates with Hochiki Model FireNET Plus 1127, Fire Alarm Control Panels (FACP).

Detector base, Models YBN-NSA-4 (c) and HSB-NSA-6 (c), Model ASB (c) (d), Sounder Detector Base, Models SCI-B4 (c), and SCI-B6 (c), Isolator Detector Addressable Sounder Base (c), and Model ASBL, Low Frequency 520Hz, Addressable Detector Sounder Base (c) (d) (e).

- (a) Complimentary Listed (UROX, File S1383) as a Smoke-Automatic Fire Detector.
- (b) Complementary Listed (UQGS, File S2966) as a Heat-Automatic Fire Detector.
- (c) Complimentary Listed under UROX, File S1383, under UQGS, File S2966, and under FTAM, File S1383.
- (d) Includes integral audible signal.
- (e) Low Frequency 520Hz Detector Sounder Base, also complimentary Listed (ULSZ, File S1383) as an Audible Signal Appliance.

[Last Updated](#) on 2016-11-29

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



FWSA.EX16201 Fixed Condensed Aerosol Extinguishing System Units

[Page Bottom](#)

Fixed Condensed Aerosol Extinguishing System Units

[See General Information for Fixed Condensed Aerosol Extinguishing System Units](#)**HOCHIKI AMERICA CORP.**

EX16201

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Description	Part No.
Aerosol-generating extinguishing system unit	
condensed aerosol generator	FNX-20S
condensed aerosol generator	FNX-40S
condensed aerosol generator	FNX-80S
condensed aerosol generator	FNX-100S
condensed aerosol generator	FNX-200S
condensed aerosol generator	FNX-500S
condensed aerosol generator	FNX-1200
condensed aerosol generator	FNX-2000
condensed aerosol generator	FNX-3000
condensed aerosol generator	FNX-5700
Mounting bracket, 20 g	FNX-MB-20S
Mounting brackets, 40, 80 g	FNX-MB-4080S1/ FNX-MB-4080S2
Mounting bracket, 100, 200, 500 g	FNX-MB-125
Mounting bracket, 2000, 3000, 1200 g	FNX-MB-122030
Mounting bracket, 5700 g	FNX-MB-57
Design, Installation, Operation and Maintenance Manual, Version 1.02, dated September 2012 and revised February 2013	1700-11990

For Class A surface burning and Class B and C category hazards; not for use in hazardous (classified) locations. Temperature range -54 to +54°C.

[Last Updated](#) on 2013-07-29[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



GOAS.EX26684 Wet-chemical-solution Extinguishing System Units

[Page Bottom](#)

Wet-chemical-solution Extinguishing System Units

[See General Information for Wet-chemical-solution Extinguishing System Units](#)

HOCHIKI AMERICA CORP.

EX26684

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Avenger Series, stored-pressure wet chemical solution extinguishing system units in the following capacities: Models AK-275 (p/n AK-16921) 2.72 gal., AK-375 (p/n AK-13334) 3.75 gal., AK-475 (p/n AK-17379) 4.80 gal. and AK-675 (p/n AK-15196) 6.14 gal.

The units are designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring in restaurant hoods, plenums, filters, ducts and associated cooking appliances. For temperatures +32 to +120 F. Operated by automatic means with manual back up. Includes the protection of deep fat fryers, griddles, range tops, woks, upright broilers, electric charbroilers, rock charbroilers, natural charcoal charbroilers, mesquite wood charbroilers and gas radiant charbroilers.

A description of the extinguishing system units and the design and installation limitations are contained in the Listee's Installation Manual (HA-06-362) dated January 2015, rev. V1.00. Copies are available from the Listee.

Trademark and/or Tradename: "Avenger"

[Last Updated](#) on 2015-02-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UNI.U.S6512 Boxes, Non-coded

[Page Bottom](#)

Boxes, Noncoded

[See General Information for Boxes, Noncoded](#)

HOCHIKI AMERICA CORP.

S6512

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Analog addressable pull stations, Models DCP-AMS, DCP-AMS-KL, DCP-AMS-LP, DCP-AMS-KL-LP, DCP-FNM-AMS-KL-LP, FWC-FSLC-PULL@, FWC-FSLC-PULLK@, FWC-FSLC-PULL2@, FWC-FSLC-PULL2K@, FFO-PULL-SH, FFO-PULL-SK, FFO-PULL-DH, FFO-PULL-DK, intended for indoor use only.

Boxes, non-coded, Models HPS-CP, HPS-CP/S, HPS-DAH, -SAK, -DAH/S, -SAH, -SAK, -SAH-WP, DA-C, DA-C/S, FWC-CNV-PULL@, FWC-CNV-PULL2@, FWC-CNV-PULLK@, FWC-CNV-PULL2K@.

Model HPS-DAK-SR.

@ - Napco Security Systems Inc. models.

Trademark and/or Tradename: "S6512"

[Last Updated](#) on 2015-01-22

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



SYSW.S5694 Accessories, Releasing Device

[Page Bottom](#)

Accessories, Releasing Device

[See General Information for Accessories, Releasing Device](#)

HOCHIKI AMERICA CORP.

S5694

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Manual extinguishant disablement switches, Model(s) HCVR-DS-R, HCVR-DS-C+.

Releasing module, Model HCVR-SQA+

Special cable assembly+ Complementary Listed under UOXX.

[Last Updated](#) on 2013-08-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



SYZV.S6468 Control Units, Releasing Device

[Page Bottom](#)

Control Units, Releasing Device

[See General Information for Control Units, Releasing Device](#)

HOCHIKI AMERICA CORP.

S6468

Suite 100

7051 VILLAGE DR

Buena Park, CA 90621 USA

Releasing Panel Model(s) HCVR-3-C or -G (115V), HCVR-3-C or -G (230V), HCVR-3-R (115V), HCVR-3-R (230V)

Subassembly, Enclosure Back Box Model(s) HCVR-3-ENC-BC followed by -R,-C or -G

[Last Updated](#) on 2016-08-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



UEHX.E349118 Signal Appliances, Miscellaneous

[Page Bottom](#)

Signal Appliances, Miscellaneous

[See General Information for Signal Appliances, Miscellaneous](#)

HOCHIKI AMERICA CORP.

E349118

Suite 100

7051 VILLAGE DR

Buena Park, CA 90621 USA

"Type NM" Signaling station, Models PB-SA. All stations with covers may be used outdoors in ambients not to exceed -40F to 150F.

[Last Updated](#) on 2011-09-01

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UEHX7.E349118
Signal Appliances, Miscellaneous Certified for Canada

[Page Bottom](#)

Signal Appliances, Miscellaneous Certified for Canada

[See General Information for Signal Appliances, Miscellaneous Certified for Canada](#)

HOCHIKI AMERICA CORP.

E349118

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

"Type NM" Signaling station, Models PB-SA. All stations with covers may be used outdoors in ambients not to exceed -40 to 66C.

[Last Updated](#) on 2011-09-01

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UHMV.E236171
Fire Alarm Devices for Use in Hazardous Locations

[Page Bottom](#)

Fire Alarm Devices for Use in Hazardous Locations

[See General Information for Fire Alarm Devices for Use in Hazardous Locations](#)

HOCHIKI AMERICA CORP.

E236171

Suite 100

7051 VILLAGE DR

Buena Park, CA 90621 USA

Class I, Groups B, C and D; Class II, Groups E, F and G.

Fire alarm/initiating station, Model HPS-SA-EX/WP.

[Last Updated](#) on 2009-12-02

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



**ULSZ.S1529
Audible-signal Appliances**

[Page Bottom](#)

Audible-signal Appliances

[See General Information for Audible-signal Appliances](#)

HOCHIKI AMERICA CORP.

S1529

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Accessories, Models HGOE-R, HGOE-W, HSB-R, HSB-W, HCSB-R, HCSB-W.

Horns, Models HEH24-WR, HEH24-WW, indoor use only.

Models HX91-R, HX91-W, HX93-R, HX93-W, intended for indoor use; Model HGOE for outdoor use.

Horn/strobes, Models HCC24CR, HCC24CW, HCC24PCR, HCC24PCW ceiling horn/strobe.

Models HEC3-24WR, HEC3-24WW, HEC3-24PWR, HEC3-24PWW, HEC3-12WR, HEC3-12WW, HEC3-12PWR, HEC3-12PWW, multi-candella horn strobe, intended for indoor use, wall mount.

Models HEC24-1575WR, HEC24-1575WW, HEC24-1575PWR, HEC24-1575PWW, HEC24-177WR, HEC24-177WW.

Strobe lights, Models WHEC24-75WR, WHEC24-75WW. Intended for indoor use on a wall. May be used for outdoor applications only when combined with enclosure Model HGOE.

		Enclosure Ratings	
Device	Model	Type Rating Per UL 50	IEC "IP" Rating
Bell	B6-24, B10-24	Indoor	— —
Bell	BB-WP	Outdoor	— —

[Last Updated](#) on 2013-11-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



**UOJZ.S6468
Control Units, System**

[Page Bottom](#)

Control Units, System

[See General Information for Control Units, System](#)

HOCHIKI AMERICA CORP.

S6468

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

UL 864 9th Edition Listed

Model	Control Unit System Type(s)	Initiating Device Type(s)	Signaling Type(s)
Control Unit			
HCVX-2R /115V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVX-2R /230V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVX-4R /115V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVX-4R /230V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVX-8R /230V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVXD-2R /115V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVXD-2R /230V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVXD-4R /115V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVXD-4R /230V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVXD-8R /115V	L, P (PPU), RS (PPU)	A, M	DAC, NC
HCVXD-8R /230V	L, P (PPU), RS (PPU)	A, M	DAC, NC
FireNET 2127 (+), FireNET 4127 (+), Model FN-X Y ZAECS-V - Where X can be 2, 4, LCD or LCT. Where Y can be 127, S, or N. Where Z can be SP or US. Where A can be 0-3, 5, 6, or 8. Where E may be E or O. Where C can be R, C or G. Where S can be S, D, P, DP, N, or NP. Where V can be 024, 120, or 220			
	L	A, M, WF	March, NC
	AUX	A, M, SS, WF	NC
	RS (PPU)	A, M, SS, WF	DAC, OT
	P (PPU)	A, M, SS, WF	C, MX, NC, OT
	CS (PPU)	A, M, SS, WF	DAC, OT
FireNET Plus(+), Model FNP-x127US or SP, followed by fecs - Where x can be 1, 2; Where f can be 0,1,2,4; Where e can be E or O; Where c can be R, C or G; Where s can be S, D, or L.			
	L	A, M, SS, WF	March, NC
	AUX	A, M, SS, WF	NC
	RS (PPU)	A, M, SS, WF	DAC, OT
	P (PPU)	A, M, SS, WF	C, MX, NC, OT
	CS (PPU)	A, M, SS, WF	DAC, MX, OT
FNM2127-R, FNM2127-G	L	A, M, SS, WF	March, NC
	AUX	A, M, SS, WF	NC
	RS (PPU)	A, M, SS, WF	DAC, OT

	P (PPU)	A, M, SS, WF	C, MX, NC, OT
	CS (PPU)	A, M, SS, WF	DAC, MX, OT
HCP-1000	L	A, M, SS, WF	March, NC
	AUX, RS (PPU)	A, M, WF	NC, Rev Pol
HCP-1008EDS	L	A, M, SS, WF	March, NC
	AUX, RS (PPU)	A, M, WF	NC, Rev Pol
HCVR-3-R (115V), HCVR-3-R (230V), HCVR-3-C or -G (115V), HCVR-3-C or -G (230V)			
	L	A, M	-

UL 864 9th Edition Listed

16 Channel Input Output Board, Model(s) FN-4127-IO

Subassemblies, Model(s) FN-4127-SLC, FN-4127-NIC, HBBX-1024XT, HBBX-1024DS, HMCC-1024-6DS, HMCC-1024-12DS, HMCC-1024-12XT

Subassembly, 2 Zone Dialer Board, Model(s) HA1842-00

Subassembly, 4 Zone Dialer Board, Model(s) HA1844-00

Subassembly, 8 Zone Dialer Board, Model(s) HA1848-00

Subassembly, Back Box, Model(s) HA0511-10

Subassembly, Digital Alarm Communicator, Model(s) FN-DAC

Subassembly, Enclosure Back Box, Model(s) HCVR-3-ENC-BC followed by -R, -C or -G

Subassembly, Fascia, Model(s) HA0607-10

Subassembly, Lid, Model(s) HA0613-10

Subassembly, Dialer Board, Model(s) HA1850-00

L - Local System

P (PPU) - Proprietary System (Protected Premises Unit)

RS (PPU) - Remote Station System (Protected Premises Unit)

A - Automatic Fire Alarm: thermostats, smoke detectors, etc.

M - Manual Fire Alarm: manually operated boxes

DAC - Digital Alarm Communicator

NC - Noncoded, Steady, Temporal 3 Pattern, etc.

WF - Waterflow Alarm: waterflow switches

March - March Time

AUX - Auxiliary System

SS - Supervisory: gate valves, water-level switches, temperature switches, carbon monoxide alarm, residential fire alarm control units, etc.

OT - Other Transmission Technologies

C - Coded

MX - Multiplex

CS (PPU) - Central Station System (Protected Premises Unit)

Rev Pol - Reverse Polarity

+ - Except Local Station Types, must be installed with specific Listed Device(s) indicated in the installation instructions and wiring diagrams to provide indicated type service.

NOTE - Models may be followed by -10, -20, or -40 for color of panel enclosures.

Last Updated on 2017-04-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



UOXX.S5694 Control Unit Accessories, System

[Page Bottom](#)

Control Unit Accessories, System

[See General Information for Control Unit Accessories, System](#)

HOCHIKI AMERICA CORP.

S5694

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Abort Switch, Model(s) HCVR-AS-C, HCVR-AS-R

Ancillary Board, Model(s) HCVR-AB

Ancillary Board with Enclosure, Model(s) HCVR-ABE-C, HCVR-ABE-R

Audio adjunct systems, Model(s) EVAX-100, EVAX-100E, EVAX-150, EVAX-150E, EVAX-200, EVAX-200E, EVAX-25, EVAX-25E, EVAX-50, EVAX-50E, FNV-DP, FNV-MP

Audio adjunct systems Subassemblies, Model(s) FNV-MFP, FNV-DCC, FNV-ASC, FNV-SSC, FNV-MMC, FNV-IOI, FNV-SLC, FNV-MFH, FNV-MBR, FNV-AMI, FNV-MBK, FNV-FO, FNV-BA, FNV-PWR, FNV-BRK, FNV-LLC, FNV-ISO

Bell modules, "S5694", Model(s) CHQ-BM

Bell modules, Model(s) DCP-SOM, FFO-OM, FWC-FSLC-SOM1

City Tie Module, Model(s) FN-CTM

Class A output modules, Model(s) DCP-SOM-A, DCP-SOM-AI

Contact module, Model(s) DCP-FNM-FRCMA, DCP-FRCMA, DCP-FRCMA-I

Conventional Zone Modules, Model(s) DCP-CZM, FFO-ZM, FWC-FSLC-CZM

Detector isolator, Model(s) SCI-B6

Detector isolator bas, Model(s) SCI-B4

eView-M Remote Annunciator, Model(s) FNM-LCD-S-C, FNM-LCD-S-R

Fire Alarm Equipment, Model(s) FN-LCD N USAEC-024 where "A" can be 0 or 1 and the second "C" can be R, C, or G

PE-10SN, PE-6SN

Fireman's Handset, Model(s) FNV-FH

Fireman's phone jacks, Model(s) FNV-FJ

Fireman's telephone stations, Model(s) FNV-FS

FireNet Plus LED Graphix Display, Model(s) FNP-LED-AB-CDE where A is either 0, 2, or 3 and denotes enclosure size, B is the enclosure and can be either 1 (red) or 2 (charcoal), and CDE are the number of LED expansion cards; C (red), D (green), and E (yellow). The total of C, D, & E cannot exceed 1 if A is 0, the total of C, D, & E cannot exceed 3 if A is 2, and the total of C, D, and E cannot exceed 5 if A is 3.

Keyswitch Disable Module, Model(s) SOM-R-DS

Lamp Status Unit, Model(s) HCVR-SDU-6F-C, HCVR-SDU-6F-R, HCVR-SDU-6FM-C, HCVR-SDU-6FM-R, HCVR-SDU-6S-C, HCVR-SDU-6S-R, HCVR-

SDU-6SM-C, HCVR-SDU-6SM-R

Lobby enclosures for telephone and microphone modules, Model(s) HBB-1001, HBB-1002, HBB-1003

Main annunciator chassis, Model(s) HRAM-1032, HRAM-1032TZDS

Main enclosures, Model(s) EVX-CAB2

Manual Extinguishant Disablement Switch, Model(s) HCVR-DS-R, HCVR-DS-C

Media (Serial to Fiber optic) converter, Model(s) TCF-142-M-ST

Monitor module, Model(s) DCP-FNM-DIMM, DCP-FNM-FRCME-M, DCP-FRCME-M, FWC-FSLC-EXM1B, FFO-2MM, FFO-MM4, FFO-MMMP

Monitor modules, Model(s) CHQ-CM, CHQ-CM-4, DCP-DIMM, DCP-FRCME-4, DCP-FRCME-4-100, DCP-FRCME-5-100, DCP-FRCME-P, FWC-FSLC-EZM1, FWC-FSLC-EZM2

NAC power extenders, Model(s) FN-1042-ALADA-R, FN-1042-UL2ADA-C, FN-1042-UL2ADA-R, FN-1042-ULADA-B, FN-1042-ULADA-C, FN-1042-ULADA-G, FN-642-UL2ADA-C, FN-642-UL2ADA-R, FN-642-ULADA-B, FN-642-ULADA-C, FN-642-ULADA-G, FN-642-ULADA-R, FN-842-UL2ADA-C, FN-842-UL2ADA-R, FN-842-ULADA-B, FN-842-ULADA-C, FN-842-ULADA-G, FN-842-ULADA-R

Relay modules, Model(s) DCP-FNM-R2ML, DCP-R2M, DCP-R2MH, DCP-R2MH-I, DCP-R2ML, DCP-R2ML-I, DCP-RM, FFO-2RM, FWC-FSLC-RM2

Releasing Module, Model(s) HCVR-SQA

Releasing modules, Model(s) DCP-SOM-R, DCP-SRM

Remote annunciators, Model(s) EMS Graphix, Supplemental Use, FFO-LCD-S-R, FFO-LCD-S-C

FN-LCD-N-C, FN-LCD-N-R, FN-LCD-S-R, FN-LCD-S-C

FN-X Y ZAEC-V Where X can be LCD. Where Y can be N or S. Where Z can be US. Where A can be 0, 1, 6 or 8.. Where E is expandable. Where C can be R or C. Where V can be 024

HRA-1000 Series, HRAM-208*, HRTI-1*

Remote microphones, Model(s) EVX-RM

Short circuit isolators, Model(s) CHQ-SCI-A, DCP-SCI, FFO-SCIM, FWC-FSLC-ISO

Surface enclosures, Model(s) EVX-CAB3

Telephone storage cabinets, Model(s) FNV-TC

Warden's telephone stations, Model(s) FNV-WS

Trademark and/or Tradename: "S5694"

Last Updated on 2015-03-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UOXX2.S5694 Control Unit Accessories, System - Component

[Page Bottom](#)

Control Unit Accessories, System - Component

[See General Information for Control Unit Accessories, System - Component](#)

HOCHIKI AMERICA CORP.

S5694

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Audio adjunct modules, Model(s) FNV-100E, FNV-25E, FNV-50E

Bell modules, Model(s) CHQ-BM

Control modules, Model(s) CHQ-CM, CHQ-CM-4

Input Interface module, Model(s) EVX-IL8

Output I interface module, Model(s) EVX-OL8

Switch/LED Card, Model(s) EVX-SL8

Zone splitter modules, Model(s) EVX-2ZA, EVX-4Z, EVX-ZM

Marking: Company name and model designation.

[Last Updated](#) on 2014-10-30

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UQGS.S2966 Heat-automatic Fire Detectors

[Page Bottom](#)

Heat-automatic Fire Detectors

[See General Information for Heat-automatic Fire Detectors](#)

HOCHIKI AMERICA CORP.

S2966

Suite 100

7051 VILLAGE DR

Buena Park, CA 90621 USA

					Spacing (Ft)	
Model No.	Type	Compatibility Restrictions	Contact Arrangement	Temp Range (°F)	Smooth Ceiling	to Wall or Partition
ACA-V,-W (a)	FT	D2	-	135 - 150	50	25
ACB-EA	FT/ROR	D2	-	135-165	50	25
				175-190	50	25
ACB-EAW (b)	FT/ROR	D2	-	135-165	50	25
				175-190	50	25
ATD-EA	FT	None	NO	134-149	50	25
ATG-EA, FWC-FSLC-HEAT@, FFO-HEAT						
	FT	None	-	135-150	70	25
ATJ-EA (c)	FT/ROR	D2	-	135-194	70	35
DCD-135,-W	FT/ROR	None	NO	135	70	25
DCD-190,-W	FT/ROR	None	NO	190	70	25
DFE-135,-W	FT	None	NO	190	50	25
DFE-190,-W	FT	None	NO	190	50	25
DSC-EA,-W	FT, ROR	None	NO	190	50	25

Base Model	Related Detector	Control Unit Compatibility Restrictions
HSB-100	DSC-EA	None
HSB-NSA-6, YBN-NSA-4,		
	ATG-EA, FWC-FSLC-HEAT@, FFO-HEAT, ACB-EA, ATJ-EA	B2
HSC-21L, HSC-220L, HSC-221L, HSC-224L, HSC-225L		
	DFE-135, DFE-190	None
HSC-220R, HSC-221R, HSC-224R/RA, NS4-100, NS4-220, NS4-221, NS4-224, NS6-100, NS6-220, NS6-221, NS6-224		
	DCD-135, DCD-190	None
YBA-R/3	DFE-135, DFE-190	None
YBF-RL/4H5US	DFE-135, DFE-190	None
YBJ-RL/2ND, HSB-DCP-6		
	ATD-EA	None

YBN-R/2NA, ASB, FFO-SBASE		
	ATG-EA, FWC-FSLC-HEAT@, FFO-HEAT	None
AMU-B2 (addressable)	DFE-135, DFE-190	None
HS-2, HS-2L, HS-22, HS-24, HS-100, HS-220, HS-221, HS-224, HS-224L, HS-225		
	DFE-135, DFE-190	None
SCI-B4,-W, SCI-B6,-W	ACA-V, ATG-EA	B2
YBN-R/NA	ACB-EAW	B2

B2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

D2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

FT - Fixed temperature

FT/ROR - Fixed temperature/rate of rise combination

ROR - Rate of rise

(a) - Complimentary Listed (UROX, File S1383) as a Smoke-Automatic Fire Detector

(b) - For outdoor use.

(c) - Detector may be set for FT [Mode 0], FT/15° ROR [Mode 1] or 15° ROR [Mode 2] Operation.

@ - Napco Security Systems Inc. models.

Trademark and/or Tradename: "S2966"

Last Updated on 2013-03-06

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UROX.S1383 Smoke-automatic Fire Detectors

[Page Bottom](#)

Smoke-automatic Fire Detectors

[See General Information for Smoke-automatic Fire Detectors](#)

HOCHIKI AMERICA CORP.

S1383

Suite 100

7051 VILLAGE DR

Buena Park, CA 90621 USA

Detector	Application	Type	Compatibility Restrictions	Velocity Range (fpm)		Date of Manufacture	Time of Manufacture Firmware Version	Firmware Version Update
				Min	Max			
ACA-V,-W(d)	OAP, D, D (I)	P	D2	0	4000	-	-	-
ACC-V, ACC-V (WHT)	OAP, D, D (I)	P	D2	0	4000	-	-	-
ACD-V (d), (f)	OAP, D(I)	P	D2	0	4000	-	-	-
ACD-VW(d), (f)	OAP, D(I)	P	D2	0	4000	-	-	-
AIE-EA	OAP	I	D2	0	300	-	-	-
ALE-EA	OAP	P	D4	0	300	-	-	-
ALG-DH, ALG-EA, FFO- DH	OAP	P	D2	0	300	-	-	-
ALG-V	OAP	P	D2	0	4000	-	-	-
ALK-D,FWC-FSLC- SMKALG (a)	D	P	D2	0	4000	-	-	-
ALK-V,-W, ALK-V2,-W, FFO-SMOKE	OAP	P	D2	0	4000	-	-	-
ALN-V, ALN-V (WHT) FWC-FSLC-SMK (a)	OAP, D, D (I)	P	D2	0	4000	-	-	-
DH-98A, DH-98AR, DH-98ASK, DH-98-ARSK, FWC-FSLC-DUCT (a), FFO-DUCT, FFO-DUCTR								
	D(ST)	I	D2	300	4000	-	-	-
DH-98I, DH-98HVI	D(ST)	I	None	300	4000	-	-	-
DH-98P, DH-98HVP	D(ST)	P	None	300	4000	-	-	-
DH-99-A, DH-99-AR	D(ST)	P	D2	300	4000	-	-	-
FireOptix 100M	OAP	PB	None			-	-	-
FireOptix 50M	OAP	PB	None			-	-	-
FireOptix 50MA	OAP	PB	None			-	-	-
FNM-ACA-V(d)	OAP, D	P	D2	0	4000	-	-	-
FNM-ALK-V	OAP, D	P	D2	0	4000	-	-	-
SIH-24F, SIH-24FAP, SIH-24DH, SIJ-24, SIJ-24DH								
	OAP	I	D2	0	300	-	-	-
SLR-24, SLR-24DH, SLR-24H, SLR-835 (b), SLR-835B-2 (b), LSR-1224B-2W								
	OAP	P	D6	0	1000	-	-	-

SLR-24V, SLR-24VN	OAP	P	D6	0	4000	-	-	-
SLR-835B-4 (b), SLR-1224B-4W	OAP	P	D4	0	1000	-	-	-
SLR-835B-4, SLR-835B-4W	OAP	P	D4	0	300	-	-	-
SLR-835BH-4 (b), SLR-835BH-4W	OAP	P (IHD)	D4	0	1000	-	-	-
SLR-835H (b), SLR-835BH-2 (b), SLR-1224BH-2W								
	OAP	P (IHD)	D6	0	1000	-	-	-
SLV-24, SLV-24N,-W	OAP	P	D2	0	300	-	-	-
SLV-24M (c)	OAP	P	D2	0	4000	-	-	-
SLV-24V	OAP	P	D2	0	4000	-	-	-
SOC-24V	OAP, D, D (I)	P	D2	300	4000	-	-	-
SOC-24VN	OAP, D, D (I)	P	D2	300	4000	-	-	-
SOC-24VW	OAP, D, D (I)	P	D2	300	4000	-	-	-
SPB-24, SPB-24N	OAP	PB	D4			-	-	-
SPC-24	OAP	PB	D4			-	-	-
SRA-24	OAP	PB	D4			-	-	-

Base Model	Related Detector	Control Unit Compatibility Restrictions
ASB (d), (f), FFO-SBASE	ACC-V, ALG-V, AIE-EA, ATG-EA, ALK-V, ALK-V2, ALN-V, ATJ-EA, FFO-SMOKE, FFO-HEAT, ACD-V, ACD-VW	None
ASBL (e), (d), (f)	ALG-V, ALK-V, ALK-V2, ACA-V, AIE-EA, ATG-EA, ATJ-EA, ALN-V,FWC-FSLC-SMK (a), and ACC-V, ACD-V, ACD-VW	B2
FNM-NSA-4, FNM-NSA-6	YBN-NSA-4, HSB-NSA-6	B2
HSB-2, HSB-2N, HSB-21, HSB-21N, HSB-100, HSB-200, HSB-200N, HSB-220, HSB-220N, HSB-221, HSB-221N, HSB-221S, HSB-224, HSB-224N, HSB-225, HSB-225N, HSB-224, HSC-4R(b), HSC-224R(b)		
	SLG-24F, SOC-24V, SOC-24VW, SOC-24VN	B2
HSC-220R (b), HSC-221R (b), HSC-224R (b), HSC-224R/RA		
	SIJ-24, SLR-24, SLR-24H, SLR-24V, SLR-24VN, SOC-24V, SOC-24VW, SOC-24VN	B2
HSC-4R (b)	SIJ-24, SLR-24, SLR-24H, SLR-24VN, SLV-24, SLV-24V, SLV-24N, SLV-835 (b), SLV-835H (b),, SOC-24V, SOC-24VN, SOC-24VW	None
NS4-100 (b), NS4-221b(b), NS4-224 (b)		
	SLR-24, SLR-24V, SLR-24VN, SLR-24H, SLR-835 (b), SLR-835H (b), SLR-835B-4 (b), SLR-835BH-4 (b), SLR-1224B-4W, SLR-1224BH-4W, SLV-24, SLV-24V, SLV-24N, SOC-24V, SOC-24VW, SOC-VN	B2
NS4-220 (b)	SLR-24, SLR-24V, SLR-24VN, SLR-24H, SLR-835 (b), SLR-835H (b), SLR-835B-4 (b), SLR-835BH-4 (b), SLR-1224B-4W, SLR-1224BH-4W, SLV-24, SLV-24V, SLV-24N, SLV-24M, SOC-24V, SOC-24VW, SOC-24VN	B2
NS6-100 (b), NS6-220 (b), NS6-221 (b), NS6-224 (b)		
	SLR-24, SLR-24V, SLR-24VN, SLR-24H, SLR-835B-4 (b), SLR-835BH-4 (b), SLR-1224B-4W, SLR-1224BH-4W, SLV-24, SLV-24V, SLV-24N, SOC-24V, SOC-24VW, SOC-24VN	B6
NS6-220 (b)	SLR-24, SLR-24V, SLR-24VN, SLR-24H, SLR-835B-4 (b), SLR-835BH-4 (b), SLR-1224B-4W, SLR-1224BH-4W, SLV-24, SLV-24V, SLV-24N, SLV-24M, SOC-24V, SOC-24VN, SOC-24VW	B6
SBC-2 (b), SBC-2R (b)	SIJ-24, SLR-24V, SLR-835/-835W, SLR-835H/-835HW	B2

SBC-4/12 (b)	SLR-835, SLR-835WR, SLR-835H, SLR-835HW	None
SBC-4/24 (b)	SL-24V, SLR-835, SLR-835W, SLR-835H, SLR-835HW	None
SCI-B4 (d), (f),-W, SCI-B6 (d), (f),-W		
	ACD-V, ACD-VW	B3
YBJ-RL/2ND, HSB-DCP-6	ALG-EA	B4
YBN-NSA-4 (d), (f),-W, HSB-NSA-6 (d), (f),-W		
	ACD-V, ACD-VW	B2
YBN-NSA-4,-W, HSB-NSA-6,-W, FWC-FSCL-SMK6B (a), FWC-FSCL-SMK4B (a), HSC-220L,(#),HSC-221L,(#), HSC-224L, (#),HSC-225L,(#), FFO-4BASE, FFO-6BASE		
	ALG-EA, -V, AIE-EA, ALK-D, ALK-V, ALK-V2, FFO-SMOKE,FWC-FSLC-SMKALG (a)	B2

B2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

B3 - For connection to a Listed open area protection smoke or heat detector head with which compatibility was determined by test or a review of circuit parameters. Refer to the manufacturer's installation instructions for a list of compatible models.

B4 - For connection to any manufacturer's Listed compatible control unit.

B6 - This base is also suitable for connection to any manufacturer's Listed compatible control unit in a four-wire configuration, as indicated on the installation drawing of control unit and/or detector/base.

D2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

D4 - For connection to any manufacturer's Listed compatible control unit.

D6 - When using 2-wire bases Listing limited to specific system control unit. Information on compatible control unit indicated on installation drawing of control unit and/or detector. When using 4 wire bases, no restriction on compatibility.

OAP - Open Area Protection

D - Duct Detector

D(I) - Duct Detector - Installation Inside Duct

P - Photoelectric

I - Ionization

D(ST) - Duct Detector - Sampling Tubes

PB - Projected Beam

IHD - Includes Integral Heat Detector

Date of Manufacture identifies the manufacturing start date of all product models that will use the specific Time of Manufacture Firmware Version. The date of manufacture is noncoded and in the format YEAR (in 4 digits), MONTH (in letters), DAY (in 2 digits).

Time of Manufacture Firmware Version identifies a numerical and/or alphabetic series designation that is product and date-code specific and will only identify the Firmware Version at the time the product was manufactured. The numeric and/or alphabetic sequence is defined by the manufacturer.

Firmware Version Update is a numerical and/or alphabetic sequential identification that is product and date-code specific and sequentially identifies the Firmware Version Update from the previous version of firmware. The numerical and/or alphabetic sequence is defined by the manufacturer.

(a) - NAPCO Security Systems Inc. models.

(b) - May be followed by the suffix "W".

(c) - Complimentary Listed (EOOF) for Marine Applications.

(d) - Complimentary Listed (UQGS, File S2966) as a Heat-Automatic Fire Detector

(e) - Low Frequency 520Hz Detector Sounder Base, also complimentary Listed (ULSZ, File S1383) as an Audible Signal Appliance.

(f) - Complementary Listed (FTAM), File E477000) as a Gas Detector for CO gas.

Trademark and/or Tradename: "S1383"

Last Updated on 2017-05-01

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



UROX2.S1383 Smoke-automatic Fire Detectors - Component

[Page Bottom](#)

Smoke-automatic Fire Detectors - Component

[See General Information for Smoke-automatic Fire Detectors - Component](#)

HOCHIKI AMERICA CORP.

S1383

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Detector base, Model HSC-224RST.

Marking: Company name and model designation.

[Last Updated](#) on 2000-04-25

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



URRQ.S3516 Smoke-automatic Fire Detector Accessories

[Page Bottom](#)

Smoke-automatic Fire Detector Accessories

[See General Information for Smoke-automatic Fire Detector Accessories](#)

HOCHIKI AMERICA CORP.

S3516

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

End of line relay modules, Models HA-EOLR, -EOLR-12.

Smoke detector adaptor base, Model YBC-R/6, for use with C & K Systems, Inc. Model SN980-SMOKE detector for field testing with the Model TSA-B110 sensitivity tester.

Remote test switch for Model DH-98-ARSK duct detector, Model SD505-DTS-K.

Remote display units, Aspirating smoke detector accessory, Models VPR-1-RD, VPR-4-RD, VPR-6-RD, VPR-15-RD.

Smoke-automatic fire detector accessory, Model RAI-LED.

Trademark and/or Tradename: "S3516"

[Last Updated](#) on 2013-03-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



URXG.S3516 Smoke Detectors for Special Applications

[Page Bottom](#)

Smoke Detectors for Special Applications

[See General Information for Smoke Detectors for Special Applications](#)**HOCHIKI AMERICA CORP.**

S3516

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

			Compatibility	Velocity Range (fpm)	
Model	Type	Sensitivity	Restrictions	Min	Max
VPR-1	AS	N/A	None	0	300
VPR-15	AS	N/A	None	0	300
VPR-1P	AS	N/A	None	0	300
VPR-4	AS	N/A	None	0	300
VPR-6	AS	N/A	None	0	300
VPR-SD1	AS	-	D1, D3	-	-
VPR-SD2	AS	-	D1, D3	-	-

D1 - Listing limited to specific system control unit. Information on compatible control unit indicated on installation drawing of control unit and/or detector.

D3 - For connection to a Listed open area protection smoke or heat detector head with which compatibility was determined by test or a review of circuit parameters. Refer to the manufacturer's installation instructions for a list of compatible models.

AS - Air Sampling

[Last Updated](#) on 2013-02-11

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



URXG2.S3516 Smoke Detectors for Special Applications - Component

[Page Bottom](#)

Smoke Detectors for Special Applications - Component

[See General Information for Smoke Detectors for Special Applications - Component](#)

HOCHIKI AMERICA CORP.

S3516

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Air sampling smoke detectors relay modules, Model(s) VPR-CL08*, VPR-RM4*

* - Model is to be used only with the Listed models VPR.

Marking: Company name and model designation.

[Last Updated](#) on 2012-11-19

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UTRZ.S8680 Power-supply Units

[Page Bottom](#)

Power-supply Units

[See General Information for Power-supply Units](#)

HOCHIKI AMERICA CORP.

S8680

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Power supply/battery chargers. Models FN-300ULX-G, FN-300ULX-R, FN-300ULX-C, FN-300ULX-B, FN-400ULX-G, FN-400ULX-R, FN-400ULX-C, FN-400ULX-B, FN-600ULX-G, FN-600ULX-R, FN-600ULX-C, FN-600ULX-B, FN-1024ULX-G, FN-1024ULX-R, FN-1024ULX-C, FN-1024ULX-B.

[Last Updated](#) on 2005-02-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UUKC.S8369 Signaling Appliances and Equipment for the Hearing Impaired

[Page Bottom](#)

Signaling Appliances and Equipment for the Hearing Impaired

[See General Information for Signaling Appliances and Equipment for the Hearing Impaired](#)

HOCHIKI AMERICA CORP.

S8369

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Horn/strobes, Models HEC3-24WR, HEC3-24WW, HEC3-24PWR, HEC3-24PWW, HEC3-12WR, HEC3-12WW, HEC3-12PWR, HEC3-12PWW, multi-candella horn strobe, intended for indoor use, wall mount.

Models HEC24-1575WR, HEC24-1575WW, HEC24-1575PWR, HEC24-1575PWW, HEC24-177WR, HEC24-177WW.

Strobes, Models HES24-1575WRM, HES24-1575WW, HES24-177WR, HES24-177WW.

Strobe lights, synchronizable type, Models HES3-24WR, HES3-24WW, HES3-24PWR, HES3-24PWW. Selectable candela (15, 30, 60, 70 and 110 cd). Intended for indoor use on a wall.

Models HES3-12WR, HES3-12WW, HES3-12PWR, HES3-12PWW. Selectable candela (15, 30, 60 and 75 cd). Intended for indoor use on the wall.

Models HCS24CR, HCS24CW, HCS24PCR, HCS24PCW. Selectable candela (15cd, 30cd, 75cd, 95cd, 115cd, and 150cd). Intended for indoor use on a wall or a ceiling.

Sync modules, Models HAVSM-R, HAVSM-W. Intended for connection to Gentex synchronizable strobe lights for the strobe lights to be considered synchronized.

[Last Updated](#) on 2011-04-25

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



UUMW.S8370 Speakers and Amplifiers for Fire-protective Signaling Systems

[Page Bottom](#)

Speakers and Amplifiers for Fire-protective Signaling Systems

[See General Information for Speakers and Amplifiers for Fire-protective Signaling Systems](#)

HOCHIKI AMERICA CORP.

S8370

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Back boxes, Models HBLP-R, HBLP-W.

Speakers, Models HSSPKCLPR, HSSPKCLPW. Intended for Wall or Ceiling, indoor use.

Speaker/strobes, Models HSSPK24-1575WLPPW, HSSPK24-1575WLPPR, HSSPK24-1575WLPW, HSSPK24-1575WLPW. Intended for indoor use.

Models HSSPK24WLPPR, HSSPK24WLPPW, HSSPK24WLPR, HSSPK24WLPW, HSSPK24CLPPR, HSSPK24CLPPW, HSSPK24CLPR, HSSPK24CLPW.
Intended for indoor use.

[Last Updated](#) on 2011-04-25

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".

**UVAV.S3597****Visual-signal Appliances for Fire-protective Signaling Systems**[Page Bottom](#)

Visual-signal Appliances for Fire-protective Signaling Systems

[See General Information for Visual-signal Appliances for Fire-protective Signaling Systems](#)

HOCHIKI AMERICA CORP.

S3597

Suite 100
7051 VILLAGE DR
Buena Park, CA 90621 USA

Horn/strobes, Models HEC24-1575WR, HEC24-1575WW, HEC24-1575PWR, HEC24-1575PWW, HEC24-177WR, HEC24-177WW.

Strobes, Models HES24-1575WRM, HES24-1575WW, HES24-177WR, HES24-177WW.

Strobe lights, Models WHES24-75WR, WHES24-75WW, WHEC24-75WR, WHEC24-75WW.

Low frequency sounder, Models HHLFW, HHLFR.

[Last Updated](#) on 2015-05-01

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".