

SOE-24H PHOTOELECTRIC SMOKE/HEAT DETECTOR



STANDARD FEATURES

- High signal-to-noise ratio and sensitivity stability are effective in a wide range of environmental conditions
- Wide viewing angle alarm indicator
- Automatic drift compensation and maintenance indication
- Built-in magnetic test feature
- Break-away, hidden locking feature for use with NS bases
- Optimized reduction to false alarms and enhanced reaction time to real fires

DETECTOR SPACING

Smoke sensor spacing shall be in compliance with NFPA 72. For smooth ceilings and in the absence of specific performance-based design criteria, the distance between smoke sensors shall not exceed a nominal spacing of 30 ft. (9.1m) or all points on the ceiling shall have a sensor within a distance equal to or less than 0.7 times the nominal 30 ft. (9.1m) spacing. Sensors shall be located within a distance of one-half the nominal spacing, measured at right angles from all walls or partitions extending upward to within the top 15 percent of the ceiling height. For additional instructions see NFPA 72

DESCRIPTION

The SOE-24H detector is a reliable, high-quality, UL 268 7th Edition listed Photoelectric Smoke/Heat Detector allowing it to be used in all open areas and in-duct applications. The SOE-24H is a combination smoke and UL 521 7th Edition listed heat detector. The new multi-spectrum smoke categorization technology detects smoldering and flaming fires, including polyurethane fuels, while reducing nuisance cooking alarms.

OPERATION

The SOE-24H Photoelectric Smoke Detector utilizes a Green/Red LED for indication of status. In a normal standby condition the LED flashes Green every 3 seconds. When the detector senses that its sensitivity has drifted outside the UL listed sensitivity window the LED will flash Red every 3 seconds. When the detector senses smoke and activates into an alarm state, the LED will latch on Red. The detector utilizes an IR-LED and Blue LED to distinguish smoke characteristics.

PRODUCT LISTINGS



California State
Fire Marshal
7272-0410:0509

Continued next page.

SOE-24H PHOTOELECTRIC SMOKE/HEAT DETECTOR

SOE-24H Conventional Photoelectric Smoke and Heat Detector Specifications

| | | |
|--------------------------------------|---|------------------------------|
| Sensing Element | Heat | Thermistor |
| | Smoke | IR LED, Blue LED, Photodiode |
| Supply Voltage | Operating Voltage Range | 8-35VDC |
| | Absolute Max Voltage | 42VDC |
| | Maximum Voltage Ripple | 8200mVAC |
| | Maximum Input Capacitance | 0.01uF |
| Current Consumption | Standby Current | 59uA |
| | Remote Indicator Current | 8.0mA (Internally Limited) |
| | Minimum Allowable Alarm Current | 5mA |
| | Maximum Allowable Alarm Current | 150mA |
| Startup | Time | 25s (Max) |
| | Current | 160uA (Max) |
| Reset | Time | 100ms (Min) |
| | Voltage | 2.5V (Min) |
| Smoke Density Range | 1.80-3.16%/ft@ Open area | |
| | 1.80-4.55%/ft@300FPM in Duct | |
| | 1.80-3.96%/ft@1000FPM in Duct | |
| | 1.80-4.19%/ft@2000FPM in Duct | |
| | 1.80-4.07%/ft@3000FPM in Duct | |
| | 1.80-4.20%/ft@4000FPM in Duct | |
| Fixed Heat Temperature | 135°F | |
| Compatible Bases | NS4-100, NS6-100, NS4-220, NS6-220, N S4-221, NS6-221, NS4-224, NS6-224 | |
| | HSC-220R, HSC-221R, HSC-224R, HSC-4R, HSC-4R12 | |
| Operating Temperature Range | 32°F ~ 120°F (0°C ~ 49°C) | |
| UL Listed Ambient Temperature | 32°F ~ 120°F (0°C ~ 49°C) | |
| Storage Temperature Range | -22°F ~ +140°F (-30°C ~ 60°C) | |
| Operating Humidity Limit | <95%RH at 104°F (40°C), <80%RH at 120°F (49°C) | |
| Dimension | 3.94" diameter x 2.18" tall (10.0076cm x 5.54cm) | |
| Weight | 3.4 oz. (96.39g) | |
| Color | Ivory | |



PART NUMBER

(0200-11290) Conventional Multi-Criteria Smoke/Heat Detector